The Fastest Way to Start Saving Water! UP for liquid waste ۵ 000 Down for solid waste

Water Conservation Tune-Up Kit



Includes:

- Dual-Flush Handle
- Diaphragm Kit

Description

Dual-Flush Retrofit Handle and Dual Filtered 1.6 gpf/6.0 Lpf Diaphragm Kit for Exposed Water Closet Flushometers.

Specifications

Dual-Flush Retrofit Handle and Dual Filtered Diaphragm Kit for Exposed Water Closet Flushometers with the following features:

- · Retrofits to most any existing valve
- Lifting Handle UP initiates reduced flush (1.1gpf/4.2 Lpf), eliminating liquid and paper waste, saving a ½-gallon of water
- Pushing Handle DOWN initiates full flush (1.6 gpf/6.0 Lpf), eliminating solid waste and paper
- Reduces water volume by up to 30% when activated UPWARDS
- Antimicrobial Coating on Handle protects against germ transmition
- ADA Compliant Metal Non-Hold-Open Handle with Triple Seal Handle Packing
- Distinctive Green Handle signifies Water Conserving Device
- PERMEX[™] Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass (1.6 gpf/6.0 Lpf)
- Diaphragm and Handle Packing molded from PERMEX[™] Rubber Compound for Chloramine Resistance
- Includes (2) adhesive backed Metal Wall Plates etched w/Instructions

NOTES:

- NOT recommended for use on bowls with a flush volume greater than 1.6 gpf/6.0 Lpf.
- Does not include complete Flushometer valve. For complete valve, use Sloan Flushometer Models WES-111 or WES-115.



Patent Pending

This space for Architect/Engineer approval

The information contained in this document is subject to change without notice.



Made in the U.S.A. SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL. 60131 Ph: 1-800-9-VALVE-9 or 1-847-671-4300 • Fax: 1-800-447-8329 or 1-847-671-4380 www.sloanvalve.com