









Sloan<sup>®</sup> Model Flushometer



Description

Exposed Urinal Sloan<sup>®</sup> Flushometer for <sup>3</sup>/<sub>4</sub>" top spud urinals.

## Flush Cycle

□ Model 186-0.125 (0.125 gpf/0.5 Lpf) □ Model 186-0.25 (0.25 gpf/1.0 Lpf) □ Model 186-0.5 (0.5 gpf/1.9 Lpf)

## Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated High Efficiency Urinal Flushometer with the following features:

For flush volume 0.125 gpf and 0.25 gpf:

PERMEX<sup>®</sup> Synthetic Rubber Diaphragm with Dual Filtered Bypass

For flush volume 0.5 gpf:

- High Chloramine Resistant PERMEX<sup>®</sup> Synthetic Rubber Diaphragm with Linear Filtered Dual Bypass and Vortex Cleansing Action<sup>™</sup>
- ADA Compliant Metal Oscillating Non-Hold-Open Handle with Triple Seal Handle Packing
- ¾" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Vandal Resistant Stop Cap
- Adjustable Tailpiece
- Vacuum Breaker with Flush Connection
- Spud Coupling and Spud Flange for ¾" Top Spud
- Sweat Solder Adapter with Cover Tube and Cast Wall Flange
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Non-Hold-Open Handle and No External Volume Adjustment to Ensure Water Conservation
- High Efficiency flush accuracy
- Handle Packing, Stop Seat and Vacuum Breaker Molded from PERMEX<sup>®</sup> Rubber Compound for Chloramine Resistance
- 100% of the energy used in manufacturing is offset with Renewable Energy Sources
  Wind Energy

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

## Accessories

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.

## Fixtures

Consult Sloan for Sloan brand matching fixture options.





This space for Architect/Engineer approval

The information contained in this document is subject to change without notice.

SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL 60131 Ph: 1-800-9-VALVE-9 or 1-847-671-4300 • Fax: 1-800-447-8329 or 1-847-671-4380 www.sloanvalve.com

Sloan 186-HEU S.S. — Rev. 1c (06/12) Copyright © 2012 SLOAN VALVE COMPANY