# Crown® Model Flushometer

180-1.0

▶ **Description**

Exposed, Urinal Flushometer for 1¼" top spud urinals. Valve cannot be converted to exceed a low consumption flush.

▶ **Flush Cycle**

☐ Model 180-1.0 Low Consumption (1.0 gpf/3.8 Lpf)

▶ **Specifications**

Quiet, Exposed, Piston Type, Chrome Plated Urinal Flushometer with the following features:

- Fixed Volume Piston with Filtered O-ring Bypass
- ADA Compliant Metal Oscillating Non-Hold-Open Handle with Triple Seal Handle Packing
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Locking Vandal Resistant Stop Cap
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker Flush Connection with One-piece Bottom Hex Coupling Nut
- Spud Coupling and Flange for 1¼" Top Spud
- Sweat Solder Adapter with Cover Tube and Cast Set Screw Wall Flange
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Valve designed to accept Low and Ultra-Low Consumption Pistons only to ensure Water Conservation
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Handle Packing, Main Seat, Stop Seat and Vacuum Breaker molded from PERMEX™ Rubber Compound for Chloramine Resistance

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

▶ **Variations**

☐ **T**   1½" Flush Connection

▶ **Accessories**

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.

Made with Renewable Energy

Dimensions

2¼" MIN. (57 mm)

11½" (292 mm)

1" I.P.S. SUPPLY (DN 25 mm)

4¾" (121 mm)

CENTER LINE OF FIXTURE

CENTER LINE OF WASTE

FIN. FLOOR

FIN. WALL

Made In The USA

This space for Architect/Engineer approval

Job Name _____   Date _____

Model Specified _____   Quantity _____

Variations Specified _____

Customer/Wholesaler _____

Contractor _____

Architect _____

The information contained in this document is subject to change without notice.

SLOAN

SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL 60131
Ph: 1-800-9-VALVE-9 or 1-847-671-4300 • Fax: 1-800-447-8329 or 1-847-671-4380
www.sloanvalve.com